



PRY-CAM

HARVESTER



PRY-CAM HARVESTER is a device used to acquire power supply from the AC cable system and feed power to the monitoring system when a power connection is not available on site.

KEY FEATURES

- Autonomous power supply to monitoring system
- Current transformer paired with electronic converter
- Two-piece split assembly
- Waterproof case available on demand

WHY IT IS GOOD FOR YOUR BUSINESS

- Sourcing of power supply directly from the AC cable being monitored, when no other power supply is available on site
- No batteries on site, no maintenance required
- No additional civil works required



PRY-CAM

A Brand of Prysmian Group

For data-driven
power



PRY-CAM

HARVESTER



PRY-CAM HARVESTER TECHNICAL SPECIFICATIONS

PRY-CAM HARVESTER consists of a current transformer + AC/DC electronic converter (EHEU – Energy Harvester Electronic Unit)

Energy Harvester Electronic Unit

Minimum switch-on current: 110 A (5 W output)

Max primary current: 2000 A

Max output power: 18 W (at 12 V DC)

Input Type: Sinewave 50 Hz

Current Transformer

L x W x H: 275 x 259 x x 75 mm

Internal diameter: 150 mm

Waterproof case available on demand



PRY-CAM

A Brand of Prysmian Group

For data-driven
power