

# TECK90

XLPE/PVC/AIA/PVC, Power, Armored  
1000 V, CSA TECK90, Single Conductor

**Product Construction:**

**Conductor:**

- 6 AWG thru 1000 kcmil bare copper compact Class B strand

**Insulation:**

- Cross-linked Polyethylene (XLPE), Type RW90
- Color-coded: black

**Ground (Bonding) Conductor:**

- The conductor is a concentric serving of solid bare copper wires applied over the insulation

**Inner Jacket:**

- Lead-free, flame-retardant, moisture- and sunlight-resistant Polyvinyl Chloride (PVC), black

**Armor:**

- Aluminum Interlocked Armor (AIA)

**Overall Jacket:**

- Lead-free, ACID-FLAME-CHECK ✓<sup>®</sup> AG14 flame-retardant, moisture- and sunlight-resistant Polyvinyl Chloride (PVC), black

**Options:**

- Galvanized Steel Interlocked Armor (GSIA)

**Applications:**

- For exposed and concealed wiring in dry, damp or wet locations
- For use in ventilated, non-ventilated and ladder-type cable trays in dry, damp or wet locations



**Applications (cont'd.):**

- For direct earth burial (with protection as required by inspection authority)
- For wiring in all hazardous locations when used with certified HL cable glands

**Features:**

- Rated at 90°C wet or dry
- Excellent crush, oil and chemical resistance
- Provides long service life
- Cost effective alternative to installations in conduit
- Meets cold bend and impact tests at -40°C

**Compliances:**

- Industry Compliances:**
  - CSA Standard C22.2 No. 131 and No. 174
- Flame Test Compliances:**
  - CSA FT1 and FT4
  - IEEE 383 (70,000 BTU/hr)
  - UL 1581 (70,000 BTU/hr)
  - IEEE 1202 (70,000 BTU/hr) CSA FT4
  - ICEA T-30-520 (70,000 BTU/hr)

**Compliances (cont'd.):**

**Other Compliances:**

- Hazardous Location Rating: HL
- EPA 40 CFR, Part 261 for leachable lead content per TCLP method
- OSHA Acceptable
- RoHS Compliant

**Packaging:**

- For Canadian customers, lengths are provided on returnable wood or steel reels that require a deposit. Extra charges apply for lagging, pulling eyes, paralleling and plexing
- For U.S. customers, material cut to length and shipped on non-returnable wood reels, while lengths in excess of 10,000 lbs. are provided on returnable steel reels that require a deposit. Extra charges apply for cuts less than 1000 ft., lagging, pulling eyes, paralleling and plexing

CATALOG NUMBER	NO. OF COND.	COND. SIZE (AWG/kcmil)	GROUND WIRE SIZE (AWG)	MIN. AVG. INS. THICKNESS		NOMINAL DIAMETER (OVER)						COPPER WEIGHT		NET WEIGHT		AMPACITY** (30°C AMBIENT)
						INSULATION		ARMOR		CABLE		LBS/1000 FT	kg/km	LBS/1000 FT	kg/km	
						INCHES	mm	INCHES	mm	INCHES	mm					

**6 AWG THRU 1000 kcmil—SINGLE CONDUCTOR—1000 V**

11288.040600*	1	6	8	.060	1.52	0.31	7.8	0.68	17.3	0.77	19.6	137	204	320	470	105
11288.050400*	1	4	6	.060	1.52	0.35	8.8	0.73	18.6	0.81	20.6	211	314	410	610	140
11288.030300*	1	3	6	.060	1.52	0.38	9.8	0.76	19.3	0.84	21.4	244	363	450	680	165
11288.050200*	1	2	6	.060	1.52	0.42	10.5	0.78	19.8	0.87	22.1	286	426	510	760	190
11288.050100*	1	1	4	.080	2.03	0.49	12.5	0.88	22.4	0.96	24.4	390	581	680	1010	220
11288.035100*	1	1/0	4	.080	2.03	0.53	13.5	0.91	23.2	1.00	25.4	458	682	760	1130	260
11288.035200*	1	2/0	4	.080	2.03	0.58	14.7	0.95	24.1	1.04	26.4	544	810	860	1280	300
11288.035300*	1	3/0	3	.080	2.03	0.63	15.9	1.03	26.2	1.12	28.5	685	1020	1080	1610	350
11288.025400*	1	4/0	3	.080	2.03	0.69	17.5	1.08	27.5	1.17	29.7	820	1220	1270	1890	405
11288.026000*	1	250	2	.090	2.29	0.75	19.2	1.21	30.8	1.29	32.8	980	1459	1490	2210	455
11288.036200*	1	350	1	.090	2.29	0.86	21.7	1.30	33.0	1.39	35.3	1340	1994	1910	2840	570
11288.026500*	1	500	1/0	.090	2.29	0.99	25.0	1.42	36.1	1.51	38.4	1750	2604	2510	3740	700
11288.027000*	1	750	2/0	.090	2.29	1.16	29.4	1.59	40.4	1.69	43.0	2570	3825	3510	5230	885
11288.027500*	1	1000	2/0	.090	2.29	1.31	33.2	1.81	46.0	1.90	48.3	3340	4970	4430	6590	1055

Dimensions and weights are nominal; subject to industry tolerances.

\*Non-stock item; minimum runs apply. Please consult Customer Service for price and delivery.

\*\*Ampacity is based on CE Code Part 1, Table 1 (single conductor in free air) and Rule 4-004.